



3 Phase Diesel Generator

ADD1000C



THE MAIN PARAMETERS OF THE GENSET

CHARACTERISTIC	PRP*	STB**
Electrical power (kVA)	1000	1100
Electrical power (kWt)	800	880
Current Frequency (Hz)	50)
Output voltage (V)	400/230	
Power factor	0.8	8

IMPORTANT TECHNICAL PARAMETERS

MODEL	ADD1000C	
ENGINE	Cummins	
ENGINE MODEL	KTA38-G5	
CYLINDER ARRANGEMENT	V12	
ALTERNATOR	ADD Power (China)	
ALTERNATOR MODEL	CJ634E	
CONTROL PANEL	ADD Control	
LUBRICATION SYSTEM VOLUME	120 L	
COOLING SYSTEM VOLUME	180 L	
FUEL CONSUMPTION 100% POWER	214.0 L/H	
FUEL CONSUMPTION 70% LOAD	161.0 L/H	
BATTERIES	2x190 A	

DIMENSIONS

ТҮРЕ	Open	Closed
SIZE LXWXH (MM)	5430x2120x2550	6000x2350x2350
WEIGHT (KG)	7100	9800
FUEL TANK	1800	1800

The manufacturer ADD Power reserves the right to change or supplement the above technical characteristics of power plants in order to improve the quality and operational parameters of the equipment.

*PPR (Prime Power) - the rated power of the power plant when operating in such a mode, when it is the main source of electricity for a long time for at least 12 hours. It is allowed to overload the power plant, but not more than 10% within an hour.

**STB (Standby Power) - the maximum power of the power plant, which can be maintained, working in standby mode, for a short time up to 12 hours. Characterizes the ability of the station to sharply take on the load from the consumer, but it will not be able to keep it at the maximum level for a long time.

STANDARD SET OF THE POWER PLANT

- 1. Metal frame with build in fuel tank
- 2. Diesel engine with attachments
- 3. Alternator with ATS
- 4. Cooling radiator
- 5. Control Panel
- 6. Output power box
- 7. Exhaust system
- 8. Batteries
- 9. Operations Manual



Standard manufacturer's warranty ADD Power is 12 month or 1000 motor hours (whichever comes first)