



3 Phase Diesel Generator

ADD300C



THE MAIN PARAMETERS OF THE GENSET

CHARACTERISTIC	PRP*	STB**
Electrical power (kVA)	300	330
Electrical power (kWt)	240	264
Current Frequency (Hz)	5	0
Output voltage (V)	400/230	
Power factor	0.8	

IMPORTANT TECHNICAL PARAMETERS

MODEL	ADD300C
ENGINE	Cummins
ENGINE MODEL	6LTAA9.5-G1
CYLINDER ARRANGEMENT	L6
ALTERNATOR	ADD Power (China)
ALTERNATOR MODEL	CJ444D
CONTROL PANEL	ADD Control
LUBRICATION SYSTEM VOLUME	50 L
COOLING SYSTEM VOLUME	60 L
FUEL CONSUMPTION 100% POWER	58.0 L/H
FUEL CONSUMPTION 70% LOAD	44.0 L/H
BATTERIES	2x100 A

DIMENSIONS

ТҮРЕ	Open	Closed
SIZE LXWXH (MM)	2670x1000x1650	3700x1200x2100
WEIGHT (KG)	2500	2800
FUEL TANK VOLUME (L)	500	500

The manufacturer ADD Power reserves the right to change or supplement the above technical characteristics of power plants in order to improve the quality and operational parameters of the equipment.

*PPR (Prime Power) - the rated power of the power plant when operating in such a mode, when it is the main source of electricity for a long time for at least 12 hours. It is allowed to overload the power plant, but not more than 10% within an hour.

**STB (Standby Power) - the maximum power of the power plant, which can be maintained, working in standby mode, for a short time up to 12 hours. Characterizes the ability of the station to sharply take on the load from the consumer, but it will not be able to keep it at the maximum level for a long time.

STANDARD SET OF THE POWER PLANT

- 1. Metal frame with build in fuel tank
- 2. Diesel engine with attachments
- 3. Alternator with ATS
- 4. Cooling radiator
- 5. Control Panel
- 6. Output power box
- 7. Exhaust system
- 8. Batteries
- 9. Operations Manual



Standard manufacturer's warranty ADD Power is 12 month or 1000 motor hours (whichever comes first)