



3 Phase Diesel Generator

ADD550SWD



THE MAIN PARAMETERS OF THE GENSET

CHARACTERISTIC	PRP*	STB**
Electrical power (kVA)	500	550
Electrical power (kW)	400	440
Current Frequency (Hz)	5	0
Output voltage (V)	400/230	
Power factor	0.8	

IMPORTANT TECHNICAL PARAMETERS

MODEL	ADD550SWD	
ENGINE	WOLING (China)	
ENGINE MODEL	WLG510	
CYLINDER ARRANGEMENT	V12	
ALTERNATOR	ADD Power (China)	
ALTERNATOR MODEL	CJ355D	
CONTROL PANEL	ADD Control	
LUBRICATION SYSTEM VOLUME	60 L	
COOLING SYSTEM VOLUME	60 L	
FUEL CONSUMPTION 100% POWER	112.0 L/H	
FUEL CONSUMPTION 70% LOAD	78.0 L/H	
BATTERIES	2x132 A	

DIMENSIONS

ТҮРЕ	Open	Closed
SIZE LXWXH (MM)	3200x1000x1800	3900x1300x2200
WEIGHT (KG)	4300	5800
FUEL TANK VOLUME (L)	880	880

The manufacturer ADD Power reserves the right to change or supplement the above technical characteristics of power plants in order to improve the quality and operational parameters of the equipment.

*PPR (Prime Power) - the rated power of the power plant when operating in such a mode, when it is the main source of electricity for a long time for at least 12 hours. It is allowed to overload the power plant, but not more than 10% within an hour.

**STB (Standby Power) - the maximum power of the power plant, which can be maintained, working in standby mode, for a short time up to 12 hours. Characterizes the ability of the station to sharply take on the load from the consumer, but it will not be able to keep it at the maximum level for a long time.

STANDARD SET OF THE POWER PLANT

- 1. Metal frame with build in fuel tank
- 2. Diesel engine with attachments
- 3. Alternator with ATS
- 4. Cooling radiator
- 5. Control Panel
- 6. Output power box
- 7. Exhaust system
- 8. Batteries
- 9. Operations Manual



Standard manufacturer's warranty ADD Power is 12 month or 1000 motor hours (whichever comes first)