



3 Phase Diesel Generator

ADD600C



THE MAIN PARAMETERS OF THE GENSET

CHARACTERISTIC	PRP*	STB**
Electrical power (kVA)	600	660
Electrical power (kWt)	480	518
Current Frequency (Hz)	50	0
Output voltage (V)	400/230	
Power factor	0.8	

IMPORTANT TECHNICAL PARAMETERS

MODEL	ADD600C	
ENGINE	Cummins	
ENGINE MODEL	KTAA19-G5	
CYLINDER ARRANGEMENT	L6	
ALTERNATOR	ADD Power (China)	
ALTERNATOR MODEL	CJ544E	
CONTROL PANEL	ADD Control	
LUBRICATION SYSTEM VOLUME	80 L	
COOLING SYSTEM VOLUME	120 L	
FUEL CONSUMPTION 100% POWER	115.0 L/H	
FUEL CONSUMPTION 70% LOAD	85.0 L/H	
BATTERIES	2x132 A	

DIMENSIONS

ТҮРЕ	Open	Closed
SIZE LXWXH (MM)	3470x1550x2200	4300x2000x2300
WEIGHT (KG)	4190	4820
FUEL TANK VOLUME (L)	1000	1000

The manufacturer ADD Power reserves the right to change or supplement the above technical characteristics of power plants in order to improve the quality and operational parameters of the equipment.

*PPR (Prime Power) - the rated power of the power plant when operating in such a mode, when it is the main source of electricity for a long time for at least 12 hours. It is allowed to overload the power plant, but not more than 10% within an hour.

**STB (Standby Power) - the maximum power of the power plant, which can be maintained, working in standby mode, for a short time up to 12 hours. Characterizes the ability of the station to sharply take on the load from the consumer, but it will not be able to keep it at the maximum level for a long time.

STANDARD SET OF THE POWER PLANT

- 1. Metal frame with build in fuel tank
- 2. Diesel engine with attachments
- 3. Alternator with ATS
- 4. Cooling radiator
- 5. Control Panel
- 6. Output power box
- 7. Exhaust system
- 8. Batteries
- 9. Operations Manual



Standard manufacturer's warranty ADD Power is 12 month or 1000 motor hours (whichever comes first)