



3 Phase Diesel Generator

ADD700SWD



THE MAIN PARAMETERS OF THE GENSET

CHARACTERISTIC	PRP*	STB**
Electrical power (kVA)	625	700
Electrical power (kW)	500	560
Current Frequency (Hz)	5	0
Output voltage (V)	400/230	
Power factor	0.	8

IMPORTANT TECHNICAL PARAMETERS

MODEL	ADD700SWD
ENGINE	WOLING (China)
ENGINE MODEL	WLV610
CYLINDER ARRANGEMENT	V12
ALTERNATOR	ADD Power (China)
ALTERNATOR MODEL	CJ544FS
CONTROL PANEL	ADD Control
LUBRICATION SYSTEM VOLUME	60 L
COOLING SYSTEM VOLUME	60 L
FUEL CONSUMPTION 100% POWER	140.0 L/H
FUEL CONSUMPTION 70% LOAD	98.0 L/H
BATTERIES	2x132 A

DIMENSIONS

ТҮРЕ	Open	Closed
SIZE LXWXH (MM)	3500x1600x2400	4300x2000x2450
WEIGHT (KG)	4600	6100
FUEL TANK VOLUME (L)	1000	1000

The manufacturer ADD Power reserves the right to change or supplement the above technical characteristics of power plants in order to improve the quality and operational parameters of the equipment.

*PPR (Prime Power) - the rated power of the power plant when operating in such a mode, when it is the main source of electricity for a long time for at least 12 hours. It is allowed to overload the power plant, but not more than 10% within an hour.

**STB (Standby Power) - the maximum power of the power plant, which can be maintained, working in standby mode, for a short time up to 12 hours. Characterizes the ability of the station to sharply take on the load from the consumer, but it will not be able to keep it at the maximum level for a long time.

STANDARD SET OF THE POWER PLANT

- 1. Metal frame with build in fuel tank
- 2. Diesel engine with attachments
- 3. Alternator with ATS
- 4. Cooling radiator
- 5. Control Panel
- 6. Output power box
- 7. Exhaust system
- 8. Batteries
- 9. Operations Manual



Standard manufacturer's warranty ADD Power is 12 month or 1000 motor hours (whichever comes first)